

Begin Page 1 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0012 Replacing version dated / version: 22.04.2021 / 0011 Valid from: 01.11.2021 PDF print date: 01.11.2021 Pro-Line PTFE-Pulverspray

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Pro-Line PTFE-Pulverspray

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Lubricant and greasing spray Separator **Uses advised against:**

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0 Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number Emergency information services / official advisory body:

Telephone number of the company in case of emergencies: +49 (0) 700 / 24 112 112 (LMR) +1 872 5888271 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Skin Irrit.	2	H315-Causes skin irritation.
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.
Aquatic Chronic	3	H412-Harmful to aquatic life with long lasting effects.
Aerosol	1	H222-Extremely flammable aerosol.
Aerosol	1	H229-Pressurised container: May burst if heated.

2.2 Label elements Labeling according to Regulation (EC) 1272/2008 (CLP)



Page 2 of 14

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0012 Replacing version dated / version: 22.04.2021 / 0011 Valid from: 01.11.2021 PDF print date: 01.11.2021 Pro-Line PTFE-Pulverspray



Danger

H315-Causes skin irritation. H412-Harmful to aquatic life with long lasting effects. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children. P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P280-Wear protective gloves. P302+P352-IF ON SKIN: Wash with plenty of water and soap. P332+P313-If skin irritation occurs: Get medical advice / attention. P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

Without adequate ventilation, formation of explosive mixtures may be possible. Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

3.1 Substances

n.a. 3.2 Mixtures

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	
Registration number (REACH)	01-2119475514-35-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	921-024-6
CAS	
content %	15-<20
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 2, H225
	Skin Irrit. 2, H315
	STOT SE 3, H336
	Asp. Tox. 1, H304
	Aquatic Chronic 2, H411

SECTION 3: Composition/information on ingredients

Aerosol

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!



Page 3 of 14

ആ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0012 Replacing version dated / version: 22.04.2021 / 0011 Valid from: 01.11.2021 PDF print date: 01.11.2021 Pro-Line PTFE-Pulverspray

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Wash thoroughly using copious water - remove contaminated clothing immediately. If skin irritation occurs (redness etc.), consult doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available.

Ingestion

Typically no exposure pathway. Rinse the mouth thoroughly with water. Do not induce vomiting. Consult doctor immediately. Danger of aspiration.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO2 Extinction powder Unsuitable extinguishing media

n.c. 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop: Oxides of carbon Toxic gases Danger of bursting (explosion) when heated Explosive vapour/air or gas/air mixtures.

5.3 Advice for firefighters

For personal protective equipment see Section 8. In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. Full protection, if necessary. Cool container at risk with water. Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination. Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

Prevent from entering drainage system. Prevent surface and ground-water infiltration, as well as ground penetration.



Page 4 of 14

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0012 Replacing version dated / version: 22.04.2021 / 0011 Valid from: 01.11.2021 PDF print date: 01.11.2021 Pro-Line PTFE-Pulverspray

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available. Active substance:

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Keep away from sources of ignition - Do not smoke. Do not use on hot surfaces.

Do not use the product in enclosed spaces. Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work. Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Observe special regulations for aerosols!

Observe special storage conditions. Observe special storage conditions.

Keep protected from direct sunlight and temperatures over 50°C.

Store in a well ventilated place.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 1000 mg/m3

Chemical Name	Hydrocarbons, (Content %:15- <20			
WEL-TWA: 1000 mg/m3		WEL-STEL:			
Monitoring procedures:	-	Compur - KITA-	187 S (551 174)		
BMGV:				Other information: (C paragraphs 84-87, EH	o RCP-method,
Chemical Name	Butane				Content %:
WEL-TWA: 600 ppm (1450 mg/m3	3)	WEL-STEL:	750 ppm (1810 m	g/m3)	
Monitoring procedures:	-	Compur - KITA-2	221 SA (549 459)		
	-	OSHA PV2010 (n-Butane) - 1993		
BMGV:				Other information:	
Chemical Name	Isobutane				Content %:
WEL-TWA: 1000 ppm (EX) (ACGI	IH)	WEL-STEL:			
Monitoring procedures:	-	Compur - KITA-	113 SB(C) (549 368	8)	
BMGV:		•		Other information:	
Chemical Name	Propane				Content %:
WEL-TWA: 1000 ppm (ACGIH)		WEL-STEL:			



Page 5 of 14

ആ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0012 Replacing version dated / version: 22.04.2021 / 0011 Valid from: 01.11.2021 PDF print date: 01.11.2021 Pro-Line PTFE-Pulverspray

Monitoring procedures:	- Compur - KITA-125 SA (549 954)
	- OSHA PV2077 (Propane) - 1990
BMGV:	Other information:

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - oral	Long term, systemic effects	DNEL	699	mg/kg bw/d	
Consumer	Human - dermal	Long term, systemic effects	DNEL	699	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	608	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2035	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	733	mg/kg bw/d	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE).
(11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Protective nitrile gloves (EN ISO 374). Minimum layer thickness in mm:

0,5

Permeation time (penetration time) in minutes: >= 480

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time.



Page 6 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0012 Replacing version dated / version: 22.04.2021 / 0011 Valid from: 01.11.2021 PDF print date: 01.11.2021 Pro-Line PTFE-Pulverspray

Protective hand cream recommended.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: If OES or MEL is exceeded. Filter A P2 (EN 14387), code colour brown, white At high concentrations: Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138) Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

ആ

Additional information on hand protection - No tests have been performed. In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications. Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

): Stability and reactivity
Bulk density:	n.a.
Oxidising liquids:	No
	vapour/air mixture possible.
Explosives:	Product is not explosive. When using: development of explosive
9.2 Other information	
Particle characteristics:	Does not apply to aerosols.
Relative vapour density:	Does not apply to aerosols.
Density and/or relative density:	0,58 g/ml
Vapour pressure:	4100 hPa
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Solubility:	Insoluble
Kinematic viscosity:	Does not apply to aerosols.
pH:	Mixture is non-soluble (in water).
Decomposition temperature:	There is no information available on this parameter.
Auto-ignition temperature:	510 °C
Flash point:	Does not apply to aerosols.
Upper explosion limit:	32 Vol-%
Lower explosion limit:	1,4 Vol-%
Flammability:	Yes
Boiling point or initial boiling point and boiling range:	There is no information available on this parameter.
Melting point/freezing point:	There is no information available on this parameter.
Odour:	Characteristic
Colour:	White
Physical state:	Aerosol. Active substance: liquid.
	1 I

SECTION 10: Stability and reactivity

10.1 Reactivity
The product has not been tested.
10.2 Chemical stability
Stable with proper storage and handling.



Page 7 of 14

(GB)·

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0012 Replacing version dated / version: 22.04.2021 / 0011 Valid from: 01.11.2021 PDF print date: 01.11.2021 Pro-Line PTFE-Pulverspray

10.3 Possibility of hazardous reactions

Hazardous reactions will not occur during storage and handling under normal conditions.

10.4 Conditions to avoid

Heating, open flame, ignition sources Pressure increase will result in danger of bursting.

10.5 Incompatible materials

Oxidizing agents

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Hydrocarbons, C6-C7, n-alkane	es, isoalkanes	s, cyclics, <5%	% n-hexane			
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5840	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2920	mg/kg	Rat		
Acute toxicity, by inhalation:	LC50	25,2	mg/l/4h	Rat		Vapours
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Skin Irrit. 2
					Dermal	
					Irritation/Corrosion)	
Serious eye damage/irritation:						Slightly irritant
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin contact)
sensitisation:					Sensitisation)	
Specific target organ toxicity -						May cause
single exposure (STOT-SE):						drowsiness or
						dizziness.
Aspiration hazard:						Yes
Symptoms:						may cause
						headaches and
						vertigo

Butane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation Test)	
Germ cell mutagenicity:					OECD 473 (In Vitro	Negative
					Mammalian	_
					Chromosome	
					Aberration Test)	



B Page 8 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0012 Replacing version dated / version: 22.04.2021 / 0011 Valid from: 01.11.2021 PDF print date: 01.11.2021 Pro-Line PTFE-Pulverspray

Germ cell mutagenicity:				Human being	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Rat	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Aspiration hazard:						No
Symptoms:						ataxia, breathing difficulties, drowsiness, unconsciousness , frostbite, disturbed heart rhythm, headaches, cramps, intoxication, dizziness, nausea and vomiting.
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	21,394	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	

Isobutane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Acute toxicity, by inhalation:	LC50	260000	ppmV/4h	Rat		Gasses, Male
Serious eye damage/irritation:				Rabbit		Not irritant
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Aspiration hazard:						No
Symptoms:						unconsciousness , frostbite, headaches, cramps, dizziness, nausea and vomiting.
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	21,394	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	

Propane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Acute toxicity, by inhalation:	LC50	260000	ppmV/4h	Rat		Gasses, Male,
						Analogous
						conclusion
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Germ cell mutagenicity:					OECD 473 (In Vitro	Negative
					Mammalian	
					Chromosome	
					Aberration Test)	
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
5,7				typhimurium	Reverse Mutation Test)	_



B Page 9 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0012 Replacing version dated / version: 22.04.2021 / 0011 Valid from: 01.11.2021 PDF print date: 01.11.2021 Pro-Line PTFE-Pulverspray

Reproductive toxicity (Developmental toxicity):	NOAEC	21,641	mg/l		OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Aspiration hazard:					<u>_</u>	No
Symptoms:						breathing difficulties, unconsciousness , frostbite, headaches, cramps, mucous membrane irritation, dizziness, nausea and vomiting.
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	7,214	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	LOAEL	21,641	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	

11.2. Information on other hazards

Pro-Line PTFE-Pulverspray						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:	-					Does not apply to mixtures.
Other information:						No other relevant information available on adverse effects on health.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							n.d.a.
degradability:							
12.3. Bioaccumulative							n.d.a.
potential:							
12.4. Mobility in soil:							Product is
							slightly volatile.
12.5. Results of PBT							n.d.a.
and vPvB assessment							
12.6. Endocrine							n.d.a.
disrupting properties:							
12.7. Other adverse							n.d.a.
effects:							

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane



Page 10 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0012 Replacing version dated / version: 22.04.2021 / 0011 Valid from: 01.11.2021

PDF print date: 01.11.2021 Pro-Line PTFE-Pulverspray

œ

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.7. Other adverse	-						Product floats on
effects:							the water
							surface.
12.1. Toxicity to fish:	LC50	96h	11,4	mg/l	Oncorhynchus	OECD 203 (Fish,	Goldforelle
					mykiss	Acute Toxicity	(Oncorhynchus
						Test)	aguabonita)
12.1. Toxicity to fish:	NOEC/NOEL	28d	2,045	mg/l	Oncorhynchus	QSAR	
					mykiss		
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	1	mg/l	Daphnia magna	OECD 211	
						(Daphnia magna	
						Reproduction Test)	
12.1. Toxicity to daphnia:	EC50	48h	3	mg/l	Daphnia magna	OECD 202	
						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to algae:	EC50	72h	30	mg/l	Pseudokirchneriell		
					a subcapitata		
12.2. Persistence and		28d	100	%		OECD 301 F	Readily
degradability:						(Ready	biodegradable
						Biodegradability -	
						Manometric	
						Respirometry Test)	

Butane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	24,11	mg/l		QSAR	
12.1. Toxicity to daphnia:	LC50	48h	14,22	mg/l		QSAR	
12.3. Bioaccumulative potential:	Log Pow		2,98				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Isobutane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative							A notable
potential:							biological
							accumulation
							potential is not to
							be expected
							(LogPow 1-3).
12.1. Toxicity to fish:	LC50	96h	27,98	mg/l			
12.1. Toxicity to algae:	EC50	96h	7,71	mg/l			
12.2. Persistence and							Readily
degradability:							biodegradable
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance

Propane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative	Log Pow		2,28				A notable
potential:	-						biological
							accumulation
							potential is not to
							be expected
							(LogPow 1-3).



- 68							
Page 11 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0012 Replacing version dated / version: 22.04.2021 / 0011 Valid from: 01.11.2021 PDF print date: 01.11.2021							
Pro-Line PTFE-Pulverspray							
12.5. Results of PBT and vPvB assessment		No PBT substance, No vPvB substance					
SECTION 13: Disp	osal considerations						
12.4 Wests treatment motheds							
13.1 Waste treatment methods							
For the substance / mixture / residual amounts							
EC disposal code no.: The waste codes are recommendations based on the scheduled use c	f this product						
Owing to the user's specific conditions for use and disposal, other wast							
allocated under certain circumstances. (2014/955/EU)							
16 05 04 gases in pressure containers (including halons) containing ha	zardous substances						
Recommendation: Sewage disposal shall be discouraged.							
Pay attention to local and national official regulations.							
Take full aerosol cans to problem waste collection.							
Take emptied aerosol cans to valuable material collection.							
For contaminated packing material							
Pay attention to local and national official regulations.							
15 01 04 metallic packaging 15 01 10 packaging containing residues of or contaminated by hazardo	us substances						
Recycling							
Do not perforate, cut up or weld uncleaned container.							
SECTION 14. Tra	nsport information						
	isport mormation						
General statements							
14.1. UN number or ID number:	1950						
Transport by road/by rail (ADR/RID)							
14.2. UN proper shipping name: UN 1950 AEROSOLS							
14.3. Transport hazard class(es):	2.1						
14.4. Packing group:	-	•					
Classification code:	5F						
LQ: 14.5. Environmental hazards:	1 L Not applicable						
Tunnel restriction code:	D						
Transport by sea (IMDG-code)							
14.2. UN proper shipping name:		•					
AEROSOLS	0.4	<u> </u>					
14.3. Transport hazard class(es): 14.4. Packing group:	2.1						
EmS:	- F-D, S-U						
Marine Pollutant:	n.a						
14.5. Environmental hazards:	Not applicable						
Transport by air (IATA)							
14.2. UN proper shipping name:							
Aerosols, flammable 14.3. Transport hazard class(es): 2.1							
14.4. Packing group:							
14.5. Environmental hazards:	Not applicable						
14.6. Special precautions for user							
Persons employed in transporting dangerous goods must be trained.							
All persons involved in transporting must observe safety regulations. Precautions must be taken to prevent damage.							
·	instrumente						
14.7. Maritime transport in bulk according to IMC Freighted as packaged goods rather than in bulk, therefore not applical							
Minimum amount regulations have not been taken into account.							
.							



Page 12 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0012 Replacing version dated / version: 22.04.2021 / 0011 Valid from: 01.11.2021 PDF print date: 01.11.2021 Pro-Line PTFE-Pulverspray

Danger code and packing code on request. Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

ആ

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)! Regulation (EC) No 1907/2006, Annex XVII

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of	Qualifying quantity (tonnes) of
		dangerous substances as	dangerous substances as
		referred to in Article 3(10) for the	referred to in Article 3(10) for the
		application of - Lower-tier	application of - Upper-tier
		requirements	requirements
P3a	11.1	150 (netto)	500 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC):

Observe incident regulations.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

1-16

98 %

Employee training in handling dangerous goods is required. These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Skin Irrit. 2, H315	Classification according to calculation procedure.
Asp. Tox. 1, H304	Classification according to calculation procedure.
Aquatic Chronic 3, H412	Classification according to calculation procedure.
Aerosol 1, H222	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects.



Page 13 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0012 Replacing version dated / version: 22.04.2021 / 0011 Valid from: 01.11.2021 PDF print date: 01.11.2021 Pro-Line PTFE-Pulverspray

Asp. Tox. — Aspiration hazard Aquatic Chronic — Hazardous to the aquatic environment - chronic Aerosol — Aerosols Flam. Liq. — Flammable liquid STOT SE — Specific target organ toxicity - single exposure - narcotic effects

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

ആ

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany). EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

according, according to acc., acc. to ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds approx. approximately Article number Art., Art. no. ASTM ASTM International (American Society for Testing and Materials) ATE Acute Toxicity Estimate BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) **Bioconcentration factor** BCF BSEF The International Bromine Council bw body weight CAS **Chemical Abstracts Service** Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances CLP and mixtures) CMR carcinogenic, mutagenic, reproductive toxic DMEL Derived Minimum Effect Level DNEL Derived No Effect Level DOC Dissolved organic carbon dw dry weight for example (abbreviation of Latin 'exempli gratia'), for instance e.g. EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants) European Community EC ECHA European Chemicals Agency ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect European Economic Community EEC European Inventory of Existing Commercial Chemical Substances EINECS European List of Notified Chemical Substances ELINCS ΕN **European Norms** EPA United States Environmental Protection Agency (United States of America) $ErCx, E\mu Cx, ErLx (x = 10, 50)$ Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants) etc. et cetera European Union FU EVAL Ethylene-vinyl alcohol copolymer Fax. Fax number gen. general ĞHS Globally Harmonized System of Classification and Labelling of Chemicals GWP Global warming potential Koc Adsorption coefficient of organic carbon in the soil octanol-water partition coefficient Kow



ദ്ര Page 14 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0012 Replacing version dated / version: 22.04.2021 / 0011 Valid from: 01.11.2021 PDF print date: 01.11.2021 Pro-Line PTFE-Pulverspray IARC International Agency for Research on Cancer IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code) International Maritime Code for Dangerous Goods IMDG-code including, inclusive incl. **IUCLID** International Uniform Chemical Information Database IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population LD50 Lethal Dose to 50% of a test population (Median Lethal Dose) Log Koc Logarithm of adsorption coefficient of organic carbon in the soil Log Kow, Log Pow Logarithm of octanol-water partition coefficient LQ Limited Quantities MARPOL International Convention for the Prevention of Marine Pollution from Ships not applicable n.a. not available n.av. not checked n.c. n.d.a. no data available NLP No-longer-Polymer NOEC, NOEL No Observed Effect Concentration/Level OECD Organisation for Economic Co-operation and Development org. organic PBT persistent, bioaccumulative and toxic ΡE Polyethylene PNEC Predicted No Effect Concentration parts per million ppm Polyvinylchloride **PVC** REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List REACH-IT List-No. Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International RID Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern Tel. Telephone TOC Total organic carbon United Nations Recommendations on the Transport of Dangerous Goods UN RTDG VOC Volatile organic compounds very persistent and very bioaccumulative vPvB wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.