

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : OWATROL TEAK-OLJE Product code : HT01.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Paint and varnish

1.3. Details of the supplier of the safety data sheet

Registered company name : DURIEU S.A..

Address : Z.A.I. "La Marinière" 2,bis rue Charles de Gaulle.91070.BONDOUFLE.FRANCE. Telephone : + 33 (0)1.60.86.48.70. Fax : + 33 (0)1.60.86.84.84.

info@durieu.com

www.durieu.com

1.4. Emergency telephone number : + 33 (0)1.45.42.59.59.

Association/Organisation : INRS / ORFILA http://www.centres-antipoison.net.

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Repeated exposure may cause skin dryness or cracking (EUH066).

May produce an allergic reaction (EUH208).

Hazardous to the aquatic environment - Chronic hazard, Category 3 (Aquatic Chronic 3, H412).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

Additional labeling :	
EUH208	Contains BUTYLCARBAMATE DE 3-IODO-2-PROPYNYLE. May produce an allergic reaction.
Hazard statements :	
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
Precautionary statements - G	eneral :
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
Precautionary statements - Pr	revention :
P260	Do not breathe dust vapours.
P262	Do not get in eyes, on skin, or on clothing.
P273	Avoid release to the environment.
Precautionary statements - Re	esponse :
P301 + P330 + P331	IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table

The mixture satisfies neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures Composition :

•			
Identification	(EC) 1272/2008	Note	%
INDEX: PCP186	GHS08		25 <= x % < 50
EC: 918-481-9	Dgr		

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH) DWATROL TEAK-OLJE - HT01		Version 1.2 (02-05-2016) - Page 2/9
REACH: 01-2119457273-39 HYDROCARBURES C10-C13, N-ALCANES, ISOALCANES, CYCLIQUES, <2% AROMATIQUES	Asp. Tox. 1, H304 EUH:066	
INDEX: 298 EC: 918-811-1 REACH: 01-2119463583-34 HYDROCARBONS, C10, AROMATICS, <1% NAPHTALENE	GHS09, GHS07, GHS08 Dgr Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 2, H411 EUH:066	2.5 <= x % < 10
INDEX: 061 CAS: 55406-53-6 EC: 259-627-5 BUTYLCARBAMATE DE 3-IODO-2-PROPYNYLE	GHS07, GHS05, GHS09 Dgr Acute Tox. 4, H302 Skin Sens. 1, H317 Eye Dam. 1, H318 Acute Tox. 4, H332 STOT SE 3, H335 Aquatic Acute 1, H400 M Acute = 1 Aquatic Chronic 1, H410 M Chronic = 1	0 <= x % < 1

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of exposure by inhalation :

In the event of an allergic reaction, seek medical attention.

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing :

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor. Keep the person exposed at rest. Do not force vomiting.

Seek medical attention, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

This product is not classed as flammable.

5.1. Extinguishing media

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)

Unsuitable methods of extinction

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH) OWATROL TEAK-OLJE - HT01

In the event of a fire, do not use : Direct water iets

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)

- carbon dioxide (CO2)

5.3. Advice for firefighters

No data available.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Avoid any contact with the skin and eyes.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Fire prevention :

Handle in well-ventilated areas.

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Packaging

Always keep in packaging made of an identical material to the original.

Recommended types of packaging :

- Drums

- Vats

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

No data available.

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

- PVA (Polyvinyl alcohol)

Recommended properties :

- Impervious gloves in accordance with standard EN374

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact. Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Type of FFP mask :

Wear a disposable half-mask aerosol filter in accordance with standard EN149.

Category :

- FFP2

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A2 (Brown)

- B2 (Grey)

Particle filter according to standard EN143 :

- P2 (White)

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information :	
Physical state :	Fluid liquid.
Important health, safety and environmental info	ormation
pH :	Not relevant.
Boiling point/boiling range :	Not relevant.
Flash Point Interval :	60°C < PE <= 93°C
Vapour pressure (50°C) :	Not relevant.
Density :	< 1
Water solubility :	Insoluble.
Viscosity :	>20.5mm²/s (40°C)
	Method for determining the viscosity :
	ISO 3105 (Glass capillary kinematic viscometers - Specifications
	and operating instructions).
Melting point/melting range :	Not specified.
Self-ignition temperature :	Not relevant.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)	Version 1.2 (02-05-2016) - Page 5/9
OWATROL TEAK-OLJE - HT01	
Decomposition point/decomposition range :	Not relevant.
% VOC :	45
9.2. Other information	
VOC (g/l) :	450

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

Avoid :

- contact with air
- humidity

10.5. Incompatible materials

Keep away from :

- water

oxidising agents

Protéger de l'humidité. La réaction avec l'eau peut provoquer une réaction exothermique.

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO2)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness. Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

Splashes in the eyes may cause irritation and reversible damage

11.1.1. Substances

Acute toxicity :

BUTYLCARBAMATE DE 3-IODO-2-PROPYNYLE (CAS Oral route :	3: 55406-53-6) LD50 = 1056 mg/kg Species : Rat OCDE Ligne directrice 401 (Toxicité aiguë par voie orale)
Dermal route :	LD50 > 2000 mg/kg Species : Rat OCDE Ligne directrice 402 (Toxicité aiguë par voie cutanée)
HYDROCARBONS, C10, AROMATICS, <1% NAPHTAI	ENE
Oral route :	LD50 > 5000 mg/kg
	Species : Rat
	OCDE Ligne directrice 401 (Toxicité aiguë par voie orale)
Dermal route :	LD50 > 2000 mg/kg
	Species : Rabbit
	OCDE Ligne directrice 402 (Toxicité aiguë par voie cutanée)
Inhalation route (n/a) :	LC50 = 4.688 mg/l Species : Rat OCDE Ligne directrice 403 (Toxicité aiguë par inhalation)

AFETY DATA SHEET (REGULATION (EC) n° 19 WATROL TEAK-OLJE - HT01	007/2006 - REACH)	Version 1.2 (02-05-2016) - Page 6/9
	, ISOALCANES, CYCLIQUES, <2% AROMATIC LD50 > 5000 mg/kg Species : Rat OCDE Ligne directrice 401 (Toxicité	
Dermal route :	LD50 > 5000 mg/kg Species : Rabbit OCDE Ligne directrice 402 (Toxicité	é aiguë par voie cutanée)
Inhalation route (n/a) :	LC50 = 4.951 mg/l Species : Rat OCDE Ligne directrice 403 (Toxicité	é aiguë par inhalation)
Germ cell mutagenicity : HYDROCARBONS, C10, AROMATICS, <1%	NAPHTALENE No mutagenic effect.	
HYDROCARBURES C10-C13, N-ALCANES	, ISOALCANES, CYCLIQUES, <2% AROMATIC No mutagenic effect.	QUES
Carcinogenicity :		
HYDROCARBONS, C10, AROMATICS, <1% Carcinogenicity Test :	NAPHTALENE Negative. No carcinogenic effect.	
HYDROCARBURES C10-C13, N-ALCANES Carcinogenicity Test :	, ISOALCANES, CYCLIQUES, <2% AROMATIC Negative. No carcinogenic effect.	QUES
Reproductive toxicant : HYDROCARBONS, C10, AROMATICS, <1% No toxic effect for reproduction		de la toxicité pour le développement
	prénatal)	
HYDROCARBURES C10-C13, N-ALCANES No toxic effect for reproduction	, ISOALCANES, CYCLIQUES, <2% AROMATIC	QUES
	OCDE Ligne directrice 414 (Étude c prénatal)	de la toxicité pour le développement
11.1.2. Mixture		
Respiratory or skin sensitisation : Contains at least one sensitising substance. N	lay cause an allergic reaction.	
ECTION 12 : ECOLOGICAL INFORMATIC	N	
Harmful to aquatic life with long lasting effects The product must not be allowed to run into d 12.1. Toxicity		
12.1.1. Substances		
HYDROCARBONS, C10, AROMATICS, <1% Fish toxicity :	NAPHTALENE Species : Perca fluviatilis	
Crustacean toxicity :	EC50 <= 10 mg/l Species : Daphnia magna Duration of exposure : 48 h	
Algae toxicity :	ECr50 = 11 mg/l Species : Pseudokirchnerella subca Duration of exposure : 72 h	apitata

BUTYLCARBAMATE DE 3-IODO-2-PROPYNYLE (CAS: 55406-53-6)

TROL TEAK-OLJE - HT01		
Fish toxicity :	LC50 = 0.067 mg/l Species : Others Duration of exposure : 96 h	
	NOEC = 0.0084 mg/l	
	Factor $M = 1$	
	Species : Pimephales promelas Duration of exposure : 35 jours	
Crustacean toxicity :	EC50 = 0.16 mg/l Species : Daphnia magna	
	EC50 mg/l	
	Species : Daphnia magna Duration of exposure : 21 jours	
	Species : Others	
Algae toxicity :	ECr50 = 0.022 mg/l	
	Species : Scenedesmus subspicatus Duration of exposure : 72 h	
	NOEC = 0.0046 mg/l	
	Factor M = 1 Species : Scenedesmus subspicatus	
HYDROCARBURES C10-C13, N-ALCANES, ISOALC		
Fish toxicity :	LC50 = 1000 mg/l Species : Oncorhynchus mykiss	
	Duration of exposure : 96 h	
Crustacean toxicity :	EC50 = 1000 mg/l Species : Daphnia magna	
	Duration of exposure : 48 h	
Algae toxicity :	ECr50 = 1000 mg/l Species : Pseudokirchnerella subcapitata	
	Duration of exposure : 72 h	
.1.2. Mixtures		
No aquatic toxicity data available for the mixture. .2. Persistence and degradability		
	S. 55405 53 S)	
BUTYLCARBAMATE DE 3-IODO-2-PROPYNYLE (CA Biodegradability :	Rapidly degradable.	
HYDROCARBONS, C10, AROMATICS, <1% NAPHT	ALENE	
Biodegradability :	no degradability data is available, the substance degrading quickly.	is considered as not
HYDROCARBURES C10-C13, N-ALCANES, ISOALC Biodegradability :	ANES, CYCLIQUES, <2% AROMATIQUES Rapidly degradable.	
.3. Bioaccumulative potential		
	S. 55406 52 6)	
BUTYLCARBAMATE DE 3-IODO-2-PROPYNYLE (CA Octanol/water partition coefficient :	Iog Koe = 2.81	
2.4. Mobility in soil		
No data available.		
2.5. Results of PBT and vPvB assessment		

No data available.

12.6. Other adverse effects

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

Codes of wastes (Decision 2001/573/EC, Directive 2006/12/EEC, Directive 94/31/EEC on hazardous waste) :

15 01 10 * packaging containing residues of or contaminated by dangerous substances

08 01 11 * waste paint and varnish containing organic solvents or other dangerous substances

SECTION 14 : TRANSPORT INFORMATION

Exempt from transport classification and labelling.

- 14.1. UN number
- 🔂 🛛 14.2. UN proper shipping name
- 14.3. Transport hazard class(es)
- 14.4. Packing group
- 14.5. Environmental hazards
- 14.6. Special precautions for user
- -

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

- The following regulations have been used:
- EU Regulation No. 1272/2008 amended by EU Regulation No. 487/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 758/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 944/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 605/2014.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 1297/2014.
- Container information:

No data available.

- Labelling for VOCs present in varnishes, paints and in vehicle refinishing products (2004/42/EC) :

The permitted European level of VOC in this ready-to-use product is limited to 700 g/l.

The permitted European level of VOC in the ready-to-use product (category IIAf) is 700 g/l maximum (2007/2010).

- Particular provisions :

No data available.

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions. It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations. The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H302	Harmful if swallowed.
H302 + H332	Harmful if swallowed or if inhaled.
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Abbreviations :

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefahrdungsklasse (Water Hazard Class).

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.